



# N80CBMLPAL

## PNEUMATIC PALLET NAILER MACHINE MOUNTED

\*\* Note that item 30 does not include the actuator which responds to the remote signal. Customer to select the actuator required from the Operation and Maintenance Manual. An actuator is not included with the tool.

† Assemble driver to main piston and screw to feed piston rod with Loctite #271, available as part #851325 Loctite 271 Packet.

†† Loctite 242 - Available as part #851325.

## Spare Parts for N80CBMLPAL

Item#	Illus. #	Description
107490	1	GRIP,HANDLE
N80139	1	FRAME (MUSTARD YELLOW)
N70118	2	SEAL, CYLINDER CAP
105034	3	ASSEMBLY,CYLINDER CAP
N80161	4	PISTON STOP
103254	5	VALVE,HEAD
101256	6	SPRING,COMPRESSION
101236	7	O-RING,2.250X.115
MRG041630	8	O-RING,1.638X.118
T55031	9	RING, BUMPER
MSC6100-25	11	SCREW,SHCS,M6X1.00X25
MSF8125-25	13	SCREW, SFHCS M8 X 1.25X25
102506	14	COVER,EXHAUST
MPP030020	28	PIN,SPIROL M3X20MM
TVA1	30	KIT,TRIGGER VALVE
N70167	36	END CAP
103650	36	CAP,END
MRG049431	37	O-RING,2.343X.118
N70133	39	PISTON,MAIN
N80145A	39	DRIVER-PISTON ASSY.
N80154A	39	REPLACEMENT DRIVER ASSY.
851439	40	O-RING,1.689X.190
N80168	42	RING,CYLINDER
N80169	42	SEAL,CHECK
N80170	42	SLEEVE,CYLINDER
N70155	43	CYLINDER SEAL
MRG084431	46	O-RING,3.323X.122
N70156	47	BUMPER - A
N70157	48	BUMPER - B

N80354	49	GASKET, NOSE
105033	50	GUIDE,DRIVER
N80158	51	NOSE
N80119	53	PAWL, FEED
N50087	54	PIN,SPECIAL(STEP)
N80120	55	SPRING,TORSION
854004	56	WASHER
MRG009824	57	O-RING,.386X.094
N80128	58	PISTON, FEED
851384	59	O-RING,.987X.103
N80122	60	SPRING,COMPRESSION
N80123	61	BUMPER, FEED PISTON
N80124	62	COVER, FEED PISTON
851383	63	RING, RETAINING METRIC
N80125	64	PIN,SPECIAL
N80126	65	DOOR
N70149	66	PAWL CHECK
854011	67	COMPRESSION SPRING
N70140	68	PIN,SPECIAL(STEP)
N70150	69	LATCH DOOR
854013	70	SPRING,COMPRESSION
MPG030012	71	PIN, ROLL 3 X 12
MSC8125-28	72	SCREW, SHCS M8X28MM METRIC
LW14.2	92	WASHER,1/4 HI COL LOCK
MSC6100-16	93	SCREW,SHCS,M6X1.00X16
N80121	95	ROD, FEED PISTON
851880S	96	LABEL,STANLEY BOSTITCH
851817	97	LABEL,WARNING
851438	98	O-RING,2.236X.115