



A Pro Mach Operating Partner

Introducing the new VECTRA™

Low Profile Semi Automatic Medium Duty Rotary Turntable Wrapper

Maximum Load Size	55"W x 55"L x 88"H
Minimum Load Size	30"W x 30"L x 10"H
Weight Capacity	4,000 lbs. Dynamic, 20,000 lbs. Static
Utilities	115/1/60 10 Amp Electrical Service
Turntable & Drive:	65" Diameter x 3/8" Steel Plate 0-9 RPM variable speed with soft-start Dynamic positive alignment home positioning feature Chain & sprocket drive with automatic, self-adjusting chain tensioner In-line helical gear reducer on turntable drive train No-maintenance, quiet DuraGlide™ support bearings 3" Height floor to top of turntable
Control Features	CSA and UL Approved Control Panel State-of-the-Art Allen Bradley MicroLogix Programmable Logic Controller User Friendly Controls with Non-Proprietary Pushbuttons, and Switches Revo-Logic™ Exact Wrap Counting Technology Single Wrap Count Selector With The Same Settings For Top And Bottom Variable Single Speed Film Carriage Up/Down Control Film Carriage Raise/Lower Switch (Manual) Turntable Jog Pushbutton Mechanical Brake Force Adjustment on the Carriage Optional: All Colors Compatible Photocell for Automatic Load Height Detection
Film Stretch & Delivery:	Uses standard 20" film rolls Easy & Safe Threading EconoStretch film carriage
Film Carriage Drive	Heavy Duty Zero-maintenance industrial belt lift carriage Variable Speed Drive Motor UHMW Precision Carriage Guidance System
Structural Features:	All STEEL base frame and tower construction Base structure includes dual full-length steel channels Forklift portable from front or rear of machine Hinged tower for ease of transport (reduces machine profile) Adjustable, foldaway film roping bar to lock load to pallet
Ease Of Use And Safety	Fail-Safe film carriage drive with free-fall prevention Film carriage features obstacle detection with automatic shut-off Ergonomic side facing film replacement Protective cover over stretch rollers All-enclosed chains & electronics
Available Options:	VEC-010 Heavy-duty ramp for loading with pallet-jack or electric walkie VEC-100 All Colors Compatible Photocell for Automatic Load Height Detection





Film threading on the Vectra is fast and easy thanks to a hinged door design.



Simple and durable control panel makes the Vectra easy to use..



Vectra's EconoStretch carriage is raised and lowered by a durable industrial web belt for long service life and high reliability.



Orion Packaging Systems, Inc.
 A Pro Mach Operating Partner
 USA Corporate Headquarters
 100 Crescent Drive
 Collierville, TN 38017
 Toll Free (800) 333-6556
 Telephone (901) 888-4170
 Fax (901) 365-1071
 CANADA Manufacturing
 2270 Industrial Blvd
 Laval, Montreal, H7S 1P9
 Telephone (450) 667-9769
 Fax (450) 667-6320
 Email: sales@orionpackaging.com
 Web: www.orionpackaging.com

distributed by