


Fastening Solutions

Drywall to Wood




Finish: Gray Phosphate
Head: #2 Phillips Bugle
Thread: Coarse
Point: Sharp

- Coarse thread for fast drive

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/4"	#6	06A125P	1000	DS162-14V, DS200, DS200-S2, DS200-S4, DS200-AC, DS200-14V, DS202-14V, DS205-14V, DS275-18V,
		06A125PB	4000	
1 5/8"	#6	06A162P	1000	DS300-AC, DS300-24V, DS300-S2, DS300-S4
		06A162PB	4000	
2"	#7	07A200P	1000	DS200, DS200-S2, DS200-S4, DS200-AC, DS200-14V, DS202-14V, DS205-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4

Drywall to Light Gauge Steel




Finish: Gray Phosphate
Head: #2 Phillips Bugle
Thread: Fine
Point: Sharp

- Self-drilling with low-profile head

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/4"	#6	06B125P	1000	DS162-14V, DS200, DS200-S2, DS200-S4, DS200-AC, DS200-14V, DS202-14V, DS205-14V, DS275-18V,
		06B125PB	4000	
1 5/8"	#6	06B162P	1000	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4

Drywall to Heavy Gauge Steel




Finish: Clear Zinc
Head: #2 Phillips Bugle
Thread: Fine
Point: Drill

- Self-Drilling Screws point used with 33-mil (20 gauge) steel or thicker for fast penetration

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/4"	#6	06C125C	1000	DS162-14V, DS200, DS200-S2, DS200-S4, DS200-AC,
1 5/8"	#6	06C162C	1000	DS200-14V, DS202-14V, DS205-14V, DS275-18V, DS300-AC, DS300-24V, DS300-S2, DS300-S4

Cement Backer Board to Wood




Finish: Weatherex®3
Head: #2 Phillips Flat
Thread: High-Low
Point: Spoon

- Spoon point cuts through hard backer board

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/4"	#8	08T125W	1000	DS200-AC, DS200-14V, DS202-14V, DS275-18V, DS300-AC, DS300-24V, DS300-S2, DS200, DS200-S2, DS200-S4

Interior Wood to Wood




Finish: Yellow Zinc (Minimal Rust Protection)
Head: #2 Square Flat
Thread: Coarse 2/3 with wax
Point: Sharp

- Coarse thread with wax lube

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/2"	#8	08F150Y	1000	DS200, DS200-S2, DS200-S4,
1 3/4"	#8	08F175Y	1000	DS200-AC, DS200-14V, DS202-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
		08F175YB	4000	
2"	#8	08F200Y	1000	DS275-18V, DS300-AC, DS300-24V, DS300-S2, DS300-S4, DS300
2"	#10	10F200Y	800	
2 1/2"	#8	08F250Y	800	DS275-18V, DS300-AC, DS300-24V, DS300-S2, DS300-S4, DS300
3"	#8	08F300Y	800	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4

Wood Flooring (NovaDeck)




Finish: Yellow Zinc
Head: #2 Square Flat
Thread: Coarse 2/3 with wax
Point: Type 17 (Cut)

- Type 17 thread cuts fast through wood
- Wood flooring (Nova Deck) sold in 4M bulk box
- Coarse thread with wax lube

Length	Shank	Item#	Quantity	Fits Tool Model
1 3/4"	#8	08L175YB	4000	DS200, DS200-S2, DS200-S4, DS200-AC, DS200-14V, DS202-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4

Underlayment to Wood



Finish: Gray Phosphate
Head: #2 Phillips Bugle
Thread: High-Low
Point: Sharp

- Nibs under head improve screw countersink

Length	Shank	Item#	Quantity	Fits Tool Model
1 1/4"	#7	07Q125P	1000	DS200, DS200-S2, DS200-S4, DS200-AC, DS200-14V, DS202-14V, DS275-18V, DS300-AC, DS300-24V, DS300-S2, DS300-S4


Composite Decking



Finish: Weatherex®3
Head: #2 Square Mod. Trim
Thread: Coarse 2/3 with wax
Point: Type 17 (Cut)

- Coarse thread with wax lube
- Trim head helps hide screw in decking
- Corrosion resistance finish

Length	Shank	Item#	Quantity	Fits Tool Model
2"	#8	08R200W	1000	DS200-14V, DS200-AC, DS202-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
2 1/2"	#8	08R250W	800	DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
3"	#8	08R300W	800	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4




Finish: Weatherex®3, Gray and Tan finish
Head: #2 Square, Cup Anti-Mushroom
Thread: Dual Threads - Coarse and Fine
Point: X Point

- "No Mushroom" cup head helps trap material under the head for a neat appearance
- Corrosion resistance finish
- Sharp X Point drive screw with less effort

Color	Length	Shank	Item#	Quantity	Fits Tool Model
GRAY	2 1/2"	#8	08S250W003	800	DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
	3"	#8	08S300W003	800	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
TAN	2 1/2"	#8	08S250W592	800	DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
	3"	#8	08S300W592	800	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4


All Purpose Exterior Wood to Wood



Finish: Weatherex®3
Head: #2 Phillips Bugle
Thread: Coarse
Point: Sharp

- Great for trim work
- Coarse thread for fast drive
- Corrosion resistance finish

Length	Shank	Item#	Quantity	Fits Tool Model
1 5/8"	#6	06A162W	1000	DS200, DS200-S2, DS200-S4, DS200-AC, DS202-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4




Finish: Weatherex®3
Head: #2 Square Flat
Thread: Coarse 2/3 with wax
Point: Type 17 (Cut)

- Type 17 thread cuts fast through wood
- Corrosion resistance finish
- Coarse thread with wax lube

Length	Shank	Item#	Quantity	Fits Tool Model
1 3/4"	#8	08D175W	1000	DS200, DS200-S2, DS200-S4,
2"	#8	08D200W	1000	DS200-AC, DS200-14V, DS202-14V, DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
		08D250W	800	DS275-18V,
2 1/2"	#8	08D250WB	2000	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
		08D300W	800	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4
3"	#8	08D300WB	2000	DS300, DS300-AC, DS300-24V, DS300-S2, DS300-S4


Decking to Wood (Stainless Steel Screws)



Finish: Stainless Steel
Head: #2 Square Flat
Thread: Coarse 2/3 with wax
Point: Type 17 (Cut)

- 304 Stainless provide maximum corrosion resistance
- Coarse thread with wax lube
- Type 17 thread cuts fast through wood

Length	Shank	Item#	Quantity	Fits Tool Model
2 1/2"	#8	08D250S	800	DS275-18V, DS300, DS300-AC, DS300-24V, DS300-S2
3"	#9	09D300S	800	DS300-AC, DS300, DS300-24V, DS300-S2



Finish: Stainless Steel
Head: #2 Square Trim
Thread: Coarse 2/3 with wax
Point: Type 17 (Cut)

- 304 Stainless provide maximum corrosion resistance
- Trim Head helps hide screw in decking
- Coarse thread with wax lube
- Type 17 thread cuts fast through wood

Length	Shank	Item#	Quantity	Fits Tool Model
2"	#8	08R200S	1000	DS275-18V
2 1/2"	#8	08R250S	800	DS300, DS300-AC, DS300-24V, DS300-S2
3"	#9	09R300S	800	DS300, DS300-AC, DS300-24V, DS300-S2

10-DIGIT ITEM SCREW CODING SYSTEM

1 - 2 Digits Diameter	3rd Digit Application	4th - 6th Digits Length	7th Finish	8th - 10th Digits Package Color
06 #6	A Drywal to Wood	100 1" 25mm	C Zinc, clear chromate rinse	B Bulk
07 #7	B Drywal to Lt. Ga. Steel	125 1 1/4" 32mm	D Dacrotized	T Euro Tub
08 #8	C Drywal to Heavy. Ga. Steel	150 1 1/2" 38mm	G Galvanized	003 Grey
09 #9	D Decking - Wood to Wood	162 1 5/8" 41mm	P Phosphate (grey)	592 Tan
10 #10	F Flooring - Plywood to Wood	175 1 3/4" 44mm	S Stainless Steel	
	L Wood Flooring (Novadeck)	200 2" 50mm	W Weatherex 3	
	Q Underlayment	225 2 1/4" 57mm	Y Yellow Zinc	
	R Composite Decking	250 2 1/2" 65mm		
	S Composite Decking	275 2 3/4" 60mm		
	T Cement Board	300 3" 75mm		

Example: 07A200PB
07 = #7"
A = Drywall to Wood
200 = 2" SCREW
P = GREY PHOSPHATE
B = BULK PACK

Screw Characteristics by Application (3rd Digit in Item Code)

3rd Digit	Application	Head	Point	Drive	Thread	Lub.
A	Drywall to Wood	Bugle	Sharp	#2 Phillips	Coarse	None
B	Drywall to Light Ga. Steel	Bugle	Sharp	#2 Phillips	Fine	None
C	Drywall to Heavy Ga. Steel	Bugle	Self-Drilling	#2 Phillips	Fine	None
D	Decking - Wood to Wood	Flat	Type 17 Cut	#2 Phillips	Coarse 2/3	Wax
F	Flooring - Plywood to Wood	Flat	Sharp	#2 Square	Coarse 2/3	Wax
L	Wood Flooring (Novadeck)	Flat	Type 17 Cut	#2 Square	Coarse	Wax
Q	Underlayment	Mod. Trim w/Nibs	Sharp	#2 Phillips	High-Low	None
R	Composite Decking	Mod. Trim	Type 17 Cut	#2 Square	Coarse 2/3	Wax
S	Composite Decking	Anti-Mushroom	X Point	#2 Square	Coarse/Fine	None
T	Cement Board	Mod. Wafer w/Nibs	Self Drill Spoon	#2 Phillips	High-Low	None