

# PHT

## Brick

### Pneumatic Tension-Weld® Combination Tool for High-Strength Polyester Strapping



#### Reliable

Unaffected by inconsistencies in air supply, the PHT is ideal for brick plants where air quality is a problem.

#### High retained tension

The PHT's 2-1/2" L base minimizes tension loss when removed from the brick cube after strapping is applied.

#### Easy to operate and service

Simple two button operation. Tensioning, sealing and weld cooling are fully automatic, ensuring consistent joint strength regardless of operator dexterity.

Few wearing parts to service. These parts are easily replaced using a single Allen wrench.

#### High joint strength

Utilizing Signode's patented Z-Weld technology, the PHT generates the highest joint strength of any plastic strapping tool. The PHT's superior strap alignment ensures consistent weld formation.



#### Made in the U.S.A.

Supported by a nationwide service network.

### Specifications:

For use on 5/8" (16mm) high-strength polyester strapping.

Base length: 2-1/2"

Weight: 18 lbs.

**T**he PHT pneumatic sealless combination tool is designed for 5/8" (16mm) high-strength polyester strapping. Compared to other tools in its category, the PHT is lighter, more reliable and easier to operate and service. It also yields the highest joint strength and highest retained tension, making it ideal for brick cubes that shift and settle during transport.

 **SIGNODE®**

180 Hastings Drive  
Buffalo Grove, Illinois 60089