

# Titebond®

THE PRO'S ADVANTAGE™



*Franklin International*

## Titebond® Premium Polyurethane Construction Adhesive

An advanced urethane formula reinforced with the strength of Kevlar® brand fibers for unmatched strength and durability. This high performance VOC-compliant formula exceeds the requirements of the APA (American Plywood Association) AFG-01, ASTM D3498, and ASTM C557. It is waterproof, non-flammable, nontoxic and provides exceptionally strong bonds on virtually all common building materials. It is also ideal for use with non-porous substrates. For interior or exterior use, even in severe weather.

Cat. No.	Size	Units/ Case	Ctn. Lbs.	Pallet Qty.
4221	10.5 oz. Cartridge	12	13	108
4222	29 oz. Cartridge	12	36	38

Kevlar® is a registered trademark of E.I. duPont de Nemours and Company



## Titebond® Heavy Duty Construction Adhesive

Finest high-strength mastic available that exceeds the APA AFG-01 specification, D3498, FHA Use of Materials Bulletin #60, and ASTM C557. Versatile, waterproof, solvent-based adhesive that handles practically every job in construction, remodeling or repair. It is designed for a wide range of construction applications, including wet, frozen and treated lumber. It is also ideal for metal, brick, concrete, ceramics and most large panel-type substrates. It reduces the amount of nailing and helps eliminate squeaky floors.

5261	10.5 oz. Cartridge	12	11	108
5262	29 oz. Cartridge	12	30	38
25266	Gallon Can	2	20	90



## Titebond® Solvent Free Construction Adhesive

Environmentally superior with full strength versatility. VOC compliant, nontoxic, and nonflammable, it offers the peak performance of Titebond Heavy Duty Construction Adhesive. Develops 24-hour strength that surpasses other products' ultimate strength. The first solvent free adhesive to pass the APA AFG-01 specification and ASTM C557. Bonds decks, treated lumber, foamboard, paneling, and marble, as well as other common substrates. Easy to use, cleans up with water in the wet state.

7471	10.5 oz. Cartridge	12	15	108
7472	29 oz. Cartridge	12	38	38



## Titebond® Polyurethane Subfloor Adhesive

A high-performance VOC-compliant formula that exceeds the requirements of the APA AFG-01 and ASTM C557. This advanced formula is nonflammable, nontoxic, and provides exceptionally strong bonds on virtually all common building materials. It is ideal for wood, paneling, hardboard, metal, and brick. It reduces the amount of nailing and helps eliminate squeaky floors. For interior or exterior use, even in severe climates.

4772	29 oz. Cartridge	12	36	38
------	------------------	----	----	----



## Titebond® All Weather Subfloor Adhesive

An ideal choice for subfloor installations. It is designed for particleboard, OSB, engineered lumber and wet, frozen and treated lumber. It offers a strong initial tack, provides superior strength and remains permanently flexible. Excellent durability, will not become brittle. It reduces the amount of nailing and helps eliminate squeaky floors. Offers excellent cold weather extrudability down to 0° F.

5492	29 oz. Cartridge	12	30	38
------	------------------	----	----	----



## Titebond® Solvent Free Subfloor Adhesive

A high-quality, VOC-compliant formula that exceeds all requirements of APA AFG-01 specification and ASTM C557. It is designed for subfloor installations and plywood use. It reduces the amount of nailing and helps eliminate squeaky floors. An environmentally superior adhesive that contains no ozone-depleting chemicals. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.

4122	29 oz. Cartridge	12	38	38
------	------------------	----	----	----



PROFESSIONAL CONSTRUCTION ADHESIVES

titebond.com

Technical Service 800-347-4583

## Titebond® Interior/Exterior Construction Adhesive

Specifically designed for use on most common building materials including foams, plastics, wood and ceramic tile wide variety of building materials. Provides excellent water-resistance and works extremely well in colder temperatures. It also offers a 30-minute working time to allow precise placement of materials. It exceeds the performance requirements of ASTM C557.

Cat. No.	Size	Units/Case	Ctn. Lbs.	Pallet Qty.
3451	10.5 oz. Cartridge	12	11	108
3452	29 oz. Cartridge	12	31	38



## Titebond® Professional Drywall Adhesive

Designed to apply drywall to wood, hardboard, gypsum wallboard, cold-rolled steel and aluminum. Its strong initial tack allows the panels to be positioned quickly without slipping. Fills irregularities and gaps in substrates, providing a strong bond and a more solid backup surface. It is unaffected by moisture and resists aging - it will not become hard or brittle with age. It exceeds the performance requirements of ASTM C557.

5352	29 oz. Cartridge	12	32	38
------	------------------	----	----	----



## Titebond® Solvent Free Drywall Adhesive

This 100% solvent-free formula offers excellent adhesion to plaster, drywall, Gypsum wallboard, non-vinyl wallpaper, plywood, hardboard paneling, tileboard and wood. It is a VOC compliant formula containing no ozone depleting chemicals, making it safer for you and the environment. It is nonflammable, has no offensive odor and cleans up with water while wet. It exceeds the performance requirements of ASTM C557.

7272	29 oz. Cartridge	12	37	38
------	------------------	----	----	----



## Titebond® Professional Tub Surround Adhesive

This waterproof adhesive offers a strong bond yet is safe on plastics and foamboard. It is specifically formulated for the installation of PVC, HIP and ABS tub surrounds. It exceeds the performance requirements of ASTM C557 and ANSI A136.1 Type I and II water-resistance. It also offers a long working time that allows the precise positioning of the tub surround.

5221	10.5 oz. Cartridge	12	11	108
------	--------------------	----	----	-----



## Titebond® Solvent Free Cove Base Adhesive

For easy installation of rubber or vinyl cove base, this adhesive sets fast, provides a strong grab that holds materials firmly in place and eliminates sagging. It offers excellent adhesion to drywall, plaster, paint, wallpaper, paneling and ceramic tile. It is environmentally superior and contains no ozone-depleting chemicals. It is nonflammable, emits no harmful fumes and cleans up with water.

3401	10.5 oz. Cartridge	12	14	108
3402	29 oz. Cartridge	12	37	38
3405	Quart Can	6	23	112
3406	Gallon Can	2	26	90



## Titebond® Landscape Retaining Wall Adhesive

A professional-strength adhesive for use on retaining and landscape walls. It is specially formulated for use with concrete, wood, brick, masonry, pavers and most other common landscaping materials. Works well on dry, damp and cold surfaces and is strong enough to resist water and frost.

3131	10.5 oz. Cartridge	12	11	108
3132	29 oz. Cartridge	12	30	38



## Titebond® Solvent Free Fast Grab FRP Adhesive

A VOC-compliant, high-strength, and nonflammable adhesive for installing FRP panels over plywood, gypsum drywall, plaster, smooth concrete (fully cured) and other porous materials. Its solvent free formulation is safe to use and eliminates solvent odor permeability. Greatly reduces the need for bracing. Approved and endorsed by every national FRP manufacturer.

Cat. No.	Size	Units/ Case	Ctn. Lbs.	Pallet Qty.
4056	Gallon Can	2	27	90
4054	4 Gallon Plastic Pail	1	51	36



## Titebond® Solvent Based FRP Adhesive

A high-quality, versatile adhesive designed for the installation of plywood, tileboard, FRP (fiber-reinforced plastic), pre-finished hardboard, gypsum wallboard and other paneling materials. It provides excellent water-resistance and remains permanently flexible. It is easy to trowel and offers a 30-minute working time to allow precise placement of the working materials.

3222	29 oz. Cartridge	12	28	38
3227	5 Gallon Metal Pail	1	50	36



## Titebond® Solvent Free Acoustical Ceiling Tile Adhesive

Designed for the safe and easy installation of acoustical ceiling tiles. Its fast, strong grab holds materials firmly in place and eliminates potential sagging. Offers excellent adhesion to common ceiling surfaces such as drywall, plaster and paint. An environmentally superior adhesive that contains no ozone-depleting chemicals. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes, and cleans up with water. It also remains permanently flexible, offers excellent aging qualities and is unaffected by moisture.

2706	Gallon Can	2	26	90
2704	4 Gallon Plastic Pail	1	50	36



## Titebond® Trowelable Multi-Purpose Construction Adhesive

A versatile, high-quality adhesive designed for the installation of plywood, tileboard, FRP, pre-finished hardboard, gypsum wallboard, and other paneling materials. It offers excellent strength on masonry, ceramics, foamboard, plastic laminates and most rigid plastics. Provides excellent water-resistance and remains permanently flexible. Easy to trowel and offers a 30-minute working time to allow precise placement of materials. Exceeds the ASTM C557 specification.

5156	Gallon Can	2	21	90
------	------------	---	----	----



## Titebond® Fast Dry Contact Cement

A professional-quality, flammable adhesive for bonding decorative laminates, veneer, hardboard, leather, rubber, and flexible metal to most common building materials. Its solvent-based formula offers superior strength, excellent aging qualities, and becomes completely dry within 10-15 minutes of application.

5185	Quart Can	6	13	112
5186	Gallon Can	2	16	90



## Titebond® Low Solvent Neoprene-Based Contact Cement

A professional-quality, low-solvent adhesive for bonding decorative laminates, veneer, hardboard, leather, rubber and flexible metal to most common building materials. It offers a strong initial tack that allows for immediate machining. An environmentally superior adhesive that contains no ozone-depleting chemicals. Nonflammable and cleans up with water. It is the ideal choice in response to local fire codes, insurance requirements or to reduce the general risk of fire.

4155	Quart Can	6	16	112
4156	Gallon Can	2	21	90



**PROFESSIONAL SPECIALTY ADHESIVES**

titebond.com

Technical Service 800-347-4583